



Modern, sharp design, enhanced definition, robust & durable







Good

Better

Best



Good

System

CPU: Intel Celeron N2807 (Dual Core

up to 2.16Ghz

RAM: DDR III 1 Slot (upto 4GB)

LCD: 15" LED Backlight LCD (1024 x 768)

Touch: PCAP Touch

Interface

Serial: 3 Ports (RI/5V/12V Bios Selectable) (1 Port: RS-422/485 (Jumper Selectable)

USB: 2.0: 6 Ports Ethernet: 1 Port VGA: 1 Port

Drawer: 1 Port/2CH (12V/24V Selectable)

Audio: 1 Port (Line Out)

Optional

MSR: 1/2/3 Track Support (USB)

Rear Display: VFD (20CH X 2 Line, 256 x 32 Graphic). LCD (9.7", 15" Touch Option)

Wall Mount: VESA Wall Mount

Stand: V Stand

Software

OS: POSReady7/Windows 8.1 Industry Retail/Windows 10 IoT Enterprise

Power supply

DC 12V/5A (60W)

Dimension

379 (W) x 264 (H) x 362 (D)mm

Weight

6.0kg

Colour

Black

Certifications

CE/FCC/CB/CTUVus (NRTL) / RoHS/IP55

Rated

Suitable for Hospitality, Retail, Leisure & Education

We can source alternative hardware if you have seen something you like, but these are the terminals we recommend.





System

CPU: Intel N3160 (Quad Core up to 2.24Ghz)

RAM: DDR III 1 Slot (upto 8GB)

Display

LCD: 15" LED Backlight LCD (1024 x 768)

Touch: PCAP Touch

Interface

Serial: 3 Ports (RI/5V/12V Bios Selectable)

(1 Port: RS-422/485 (Jumper Selectable)

USB: 2.0: 4 Ports/3.0 2 Ports

Ethernet: 1 Port VGA: 1 Port

Drawer: 1 Port/2CH (12V/24V Selectable)

Audio: 1 Port (Line Out)

Optional

MSR: 1/2/3 Track Support (USB)

Rear Display:VFD (20CH X 2 Line, 256 x 32

Graphic). LCD (9.7", 15" Touch Option)

Wall Mount: VESA Wall Mount

Stand: V Stand

Software

OS: POSReady7/Windows 8.1 Industry

Retail/Windows 10 IoT Enterprise

Power supply

DC 12V/5A (60W)

Dimension

379 (W) x 264 (H) x 362 (D)mm

Weight

6.0kg

Colour

Black/White

Certifications

CE/FCC/CB/CTUVus (NRTL) / RoHS/IP55

Rated

Suitable for Hospitality, Retail, Leisure & Education

We can source alternative hardware if you have seen something you like, but these are the terminals we recommend. Also available in black and white.





Yuno

Best

System

CPU: Broadwell I3 5010U or BayTrail J1900

Quad-Core

RAM: DDR3 SODIMM 4 GB as standard (up to 8 GB)

SSD: 2.5" 64 GB

Display

LCD: 15" TFT (1024 x 768) or 15.6" (1366 x 768) (Y uno wide), LED back-lighting

Touchscreen: Flat, zero bezel multi-touch screen – with projected, capacitive panel (PCAP)

Brightness: 15" - 250 cd/m2; 15.6" - 200 cd/m2

Interface

Serial: 4 serial ports (+ 5/12 V power supply for

COM3 / COM4)

USB: 5 USB 2.0 ports + 1 USB 3.0 port

LAN: 10/100/1000Base-T

2nd Screen: Port with support for HDMI, DVI and

VGA (mini Display Port)

Miscellaneous

EMI: CE/FCC Class A

Safety: LVD, external adaptor UL c/us, CE, TUV, etc.

Operating Temperature: 0-40 °C Front: Dust and splash-proof Colours: Black or White

Materials: Polycarbonate (cover) + aluminium

(structure)

Dimensions: (W x D x H) - 360.1 x 171.5 x 316.1 mm

(15.1" format) 402.2 x 171.5 x 295.3 mm

(15.6" Wide format)

Weight: 10-11 kg depending on the option (15.1" format) 11-12 kg (15.6"Wide format)

Software

Windows 8 Industry, Windows 7 Pro, POS Ready 7, Linux, Androïd

Power supply

+ external 19 V DC

Optional Extras

Multi-Technology reader: for combined reading of MSR and RFID (high and low frequences), Bluetooth (BLE), NFC.

Addimat and/or Dallas readers: 1 slot, at right of

EPOS terminal

Fingerprint reader: Yes Barcode reader: 1D and 2D

Customer display: 20 characters x 2 lines (VFD) 2nd screen: 10.1" - 16:9 1024 x 600 Flat LED screen

(EPOS digital signage)

WIFI: Internal, 802.11 b/g/n

VESA fixings option(s): For wall or pole-mounted

applications (no base nor stand)

Simple screen option(s): This EPOS terminal is available in a monitor version (15.1" and 15.6"

touchscreens)

Suitable for Hospitality, Retail, Leisure & Education

We can source alternative hardware if you have seen something you like, but these are the terminals we recommend. Also available in white.



We're with you every step of the way!

Call our EPoS System Experts: 01254 881177

www.nwbm.co.uk

